

APPLICATION FOR UNITED STATES LETTERS PATENT

INVENTOR(S):     Takehiro IKEDA  
                      Ichiro OKAJIMA  
                      Narumi UMEDA

INVENTION:        MOBILE COMMUNICATION  
                      SYSTEM AND METHOD FOR  
                      CONTROLLING RECEIVING  
                      QUALITY

S P E C I F I C A T I O N

10054744-11301  
FOETIT-TH5001

SUB  
a1

This application is based on Patent Application No. 2000-347124 filed November 14, 2000 in Japan, the content of which is incorporated hereinto by reference.

5

## BACKGROUND OF THE INVENTION

### FILED OF THE INVENTION

10 The present invention relates to a mobile communication system and a method for controlling receiving quality in the mobile communication system. More specifically, the present invention relates to a mobile communication system that provides communication services from a base station to a mobile station via a radio  
15 channel and a method for controlling receiving quality in the mobile communication system.

### DESCRIPTION OF THE RELATED ART

20 In a known mobile communication system, a desired receiving quality is achieved mainly by controlling transmission power to compensate for an instantaneous variation in received signal level.

Figs. 1A to 1C show problems with receiving quality  
25 control using conventional transmission power control. It is assumed that the receiving range varies over a wide range as shown in Fig. 1A. In this case, if the

transmission power is controlled by a small step size (see Fig. 1B), transmission power control cannot follow rapid variations in receiving level. On the other hand, if the transmission power is controlled by a large step size (see Fig. 1C), transmission power control cannot accurately follow variations in receiving level.

To solve the conventional problems described with reference to Figs. 1A to 1C, the transmission power control based on a small step size must be executed at a very short control period. In this case, a new problem occurs; the overhead of a control signal for the transmission power control may reduce transmission efficiency.

In particular, it is known that the level of received signals in a mobile communication system varies very dynamically. To compensate for such received signals, the transmission power must be controlled over a wide dynamic range. Consequently, it is difficult to apply an efficient power amplifier.

## SUMMARY OF THE INVENTION

It is thus an object of the present invention to provide a mobile communication system that is adapted, in view of the above-described points, to improve the receiving quality compared to the prior art even if the instantaneous control of transmission power is not provided, as well as a method for controlling receiving

quality in the mobile communication system.

To attain this object, the present invention increases or reduces the number of base stations to simultaneously connect to a mobile station so as to realize a certain level of receiving quality control even if instantaneous control of transmission power is not executed, on the basis of the fact that when a plurality of received signals are synthesized, a variation in the level of the received signals decreases.

That is, to attain the above object, a first aspect of the present invention provides a mobile communication system comprising a plurality of base stations and a network control station conceptually located above the plurality of base stations, the network control station duplicating and/or synthesizing information in order to allow a mobile station to simultaneously communicate with at least two base stations.

The mobile station comprises means for determining, upon receiving signals from the plurality of base stations, to which base stations the mobile station is to be connected in order to satisfy a downlink receiving quality desired by the mobile station and notifying the network control station of the desired base stations to which the mobile station is to be connected. The network control station has means for transmitting a duplicated information signal to the base stations. Thus, the mobile station controls the downlink receiving quality by receiving and

synthesizing signals transmitted by the plurality of base stations.

10054741-11301  
A second aspect of the present invention provides a mobile communication system comprising a plurality of base stations, a network control station conceptually located above the plurality of base stations, the network control station duplicating and/or synthesizing information in order to allow a mobile station to simultaneously communicate with at least two base stations, and quality control means having a function of managing receiving quality of a mobile station present within a service area and a function of measuring traffic in each cell within the service area, the quality control means notifying the network control station of base stations with which the mobile station is to communicate simultaneously.

The mobile station has means for registering, in the quality control means, the downlink receiving quality desired by the mobile station and the location of the mobile station. The quality control means determines to which base stations the mobile station is to be connected in order to satisfy the receiving quality and notifies the network control station of these base stations. The network control station transmits duplicated information signal to the base stations. Furthermore, the mobile station receives and synthesizes signals transmitted by the plurality of base stations to control the downlink receiving quality.

Further, the mobile station has means for notifying, before transmitting information, the quality control means of a desired uplink receiving quality received by base stations and/or a transmittable maximum power of the mobile station and/or the location of the mobile station. The quality control means has means for identifying base stations to which the mobile station is to be connected in order to satisfy quality in such a manner that the transmittable maximum power of the mobile station is not exceeded and means for requesting the base stations and the network control station to receive and synthesize a signal from the mobile station and designating transmission power that is to be used by the mobile station. The mobile station transmits information using the designated transmission power, and the network control section synthesizes signals received by the base stations to control the uplink receiving quality.

The quality control means has means for measuring traffic in cells surrounding a cell in which the mobile station is present and means for requesting the network control station to transmit a duplicate signal to one or more stations, if any, which have a lower measured traffic and which can transmit information to the mobile station communicating in an adjacent cell. The mobile station receives and synthesizes signals from base stations that have been communicating with the mobile station and from the one or more base stations, thereby improving the

downlink receiving quality.

A third aspect of the present invention provides a receiving quality control method for a mobile communication system having a plurality of base stations within a service area wherein a network control station  
5 duplicates and/or synthesizes information in order to allow a mobile station to simultaneously communicate with at least two base stations.

The mobile station comprises means for determining,  
10 upon receiving signals from the plurality of base stations, to which base stations the mobile station is to be connected in order to satisfy a downlink receiving quality desired by the mobile station and notifying the network control station of the desired base stations to which the mobile  
15 station is to be connected. The network control station has means for transmitting a duplicated information signal to the base stations. Thus, the mobile station controls the downlink receiving quality by receiving and synthesizing signals transmitted by the plurality of base  
20 stations.

A fourth aspect of the present invention provides a receiving quality control method for a mobile communication system having a plurality of base stations within a service area wherein when a network control  
25 station duplicates and/or synthesizes information in order to allow a mobile station to simultaneously communicate with at least two base stations, the network

control station is notified of the base stations with which the mobile station is to communicate simultaneously using quality control means having a function of managing receiving quality of a mobile station present within the service area and a function of measuring traffic in each cell within the service.

The mobile station registers, in the quality control means, the downlink receiving quality desired by the mobile station and the location of the mobile station. The quality control means determines to which base stations the mobile station is to be connected in order to satisfy the receiving quality, and notifies the network control station of these base stations. The network control station transmits duplicated information signal to the base stations. The mobile station receives and synthesizes signals transmitted by the plurality of base stations to control the downlink receiving quality.

Further, before transmitting information, the mobile station notifies the quality control means of a desired uplink receiving quality received by base stations and/or a transmittable maximum power of the mobile station and/or the location of the mobile station. The quality control means identifies base stations to which the mobile station is to be connected in order to satisfy quality in such a manner that the transmittable maximum power of the mobile station is not exceeded, requests the base stations and the network control station to receive and synthesize a



signal from the mobile station, and designates  
transmission power that is to be used by the mobile station.  
The mobile station transmits information using the  
designated transmission power, and the network control  
5 section synthesizes signals received by the base stations  
to control the uplink receiving quality.

The quality control means measures traffic in cells  
surrounding a cell in which the mobile station is present,  
and requests the network control station to transmit a  
10 duplicate signal to one or more base stations, if any, which  
have a lower measured traffic and which can transmit  
information to the mobile station communicating in an  
adjacent cell. The mobile station receives and  
synthesizes signals from base stations that have been  
15 communicating with the mobile station and from the one or  
more base stations, thereby improving the downlink  
receiving quality.

A fifth aspect of the present invention provides a  
recording medium having a receiving quality control  
20 program for a mobile communication system recorded therein,  
the mobile communication system having a plurality of base  
stations within a service area, the program allowing  
execution of a step of causing a network control station  
to duplicate and/or synthesize information in order to  
25 allow a mobile station to simultaneously communicate with  
at least two base stations.

A sixth aspect of the present invention provides a

recording medium having a receiving quality control  
program for a mobile communication system recorded therein,  
the mobile communication system having a plurality of base  
stations within a service area, wherein when a network  
5 control station duplicates and/or synthesizes information  
in order to allow a mobile station to simultaneously  
communicate with at least two base stations, the program  
causes a computer to execute a step of notifying the network  
control station of the base stations with which the mobile  
10 station is to communicate simultaneously using quality  
control means having a function of managing receiving  
quality of a mobile station present within the service area  
and/or a function of measuring traffic in each cell within  
the service.

15 According to the present invention, even if  
instantaneous control of transmission power is not  
executed, the receiving quality can be improved compared  
to the prior art. In other words, the present invention  
increases or reduces the number of base stations to  
20 simultaneously connect to a mobile station so as to realize  
a certain level of receiving quality control even if  
instantaneous control of transmission power is not  
executed, on the basis of the fact that when a plurality  
of received signals are synthesized, a variation in the  
25 level of the received signals decreases.

The above and other objects, effects, features and  
advantages of the present invention will become more

apparent from the following description of embodiments thereof taken in conjunction with the accompanying drawings.

5

## BRIEF DESCRIPTION OF THE DRAWINGS

Figs. 1A to 1C are diagrams illustrating problems with receiving quality control using conventional transmission power control;

10

Fig. 2A is a diagram showing a mobile communication system for implementing receiving quality control for a downlink;

Fig. 2B is a sequence diagram showing the flow of communication control in Embodiment 1;

15

Fig. 3 is a diagram showing the signal format used in Embodiment 1;

Fig. 4A is a diagram showing another mobile communication system for implementing receiving quality control for the downlink;

20

Fig. 4B is a sequence diagram showing the flow of communication control in Embodiment 2;

Fig. 5A and 5B is a diagram showing the signal format used in Embodiment 2;

25

Fig. 6 is a chart illustrating a method by which a QoS agent selects base stations to which the mobile station is to be connected (using the locations of the base station and a mobile station);

Fig. 7A is a chart showing a past connection status history possessed by the QoS agent;

Fig. 7B is a chart illustrating a method by which the QoS agent selects base stations to which the mobile station  
5 is to be connected (using the past history);

Fig. 8A is a diagram showing a mobile communication system for implementing receiving quality control for an uplink;

Fig. 8B is a sequence diagram showing the flow of  
10 communication control in Embodiment 3;

Figs. 9A to 9D are diagrams showing the signal format used in Embodiment 3;

Fig. 10A is a diagram showing another mobile communication system for implementing receiving quality  
15 control for the downlink;

Fig. 10B is a sequence diagram showing the flow of communication control in Embodiment 4;

Fig. 11 is a diagram showing the signal format used in Embodiment 4.

20

#### DESCRIPTION OF THE PREFERRED EMBODIMENTS

Embodiments will be described below in detail with reference to Figs. 2A to 11.

25 [Embodiment 1]

Fig. 2A shows a mobile communication system for implementing receiving quality control for a downlink. In

105441-1101  
this figure, reference characters RNC, BS, and MS denote  
a radio network controller, a base station, and a mobile  
station, respectively. More specifically, Fig. 2A shows  
5 how the base station BS (including base stations #0 to #N),  
the mobile station MS#0, and the radio network control  
station RNC are connected together according to Embodiment  
1, and Fig. 2B shows the flow of communication control  
according to Embodiment 1.

10 In Embodiment 1, the mobile station MS#0 measures  
power received from surrounding base stations to determine  
to which base stations it is to be connected in order to  
satisfy a desired downlink receiving quality (step S1).

15 The mobile station MS#0 notifies the radio network  
control station RNC of the desired base stations to which  
it is to be connected, using the signal format shown in  
Fig. 3 (step S2). Fig. 3 shows the signal format used by  
the mobile station MS#0 to notify the radio network control  
station RNC (=signal indicative of information on desired  
base stations to which the mobile station is to be  
20 connected). This signal format includes an RNC address,  
a connection request command, a mobile station address,  
and information on desired bas stations to connect.

25 Upon receiving the notification from the mobile  
station MS#0, the radio network control station RNC  
duplicates a downlink transmitted signal for the mobile  
station MS#0, if any, and transmits it to the selected base  
stations (step S3). In Embodiment 1, shown in Fig. 2A,

the signal is transmitted to three base stations BS#0, #1, and #2.

The mobile station MS#0 receives signals transmitted by the base stations (step S4) and synthesizes these  
5 signals (step 5), thereby satisfying the desired downlink receiving quality.

In Embodiment 1, the mobile station MS#0 satisfies the desired quality by synthesizing the signals received from the base stations BS#0, #1, and #2, but of course the  
10 present invention is not limited to this example.

[Embodiment 2]

Fig. 4A shows another mobile communication system for implementing receiving quality control for the downlink. This system comprises a QoS (Quality of Service) agent in  
15 addition to the radio network control station RNC, the base station BS, and the mobile station MS. More specifically, Fig. 4A shows how the base station BS (including base stations #0 to #N), the mobile station MS#0, the radio network control station RNC, and the QoS agent are  
20 connected together according to Embodiment 2, and Fig. 4B shows the flow of communication control according to Embodiment 2.

In Embodiment 2, the mobile station MS#0 notifies the QoS agent of a downlink receiving quality desired thereby  
25 and the location thereof, using the signal format shown in Fig. 5A (step S11). Fig. 5A shows the signal format used by the mobile station MS#0 to notify the QoS agent

(=signal indicative of a desired receiving quality and information on the location of the mobile station). This signal format includes a QoS agent address, a connection request command, a mobile station address, a desired  
5 downlink receiving quality, and information on the location of the mobile station.

The QoS agent determines to which base stations the mobile station is to be connected in order to satisfy the quality desired by the mobile station MS#0 (step S12), and  
10 requests the radio network control station RNC to duplicate and transmit a signal to the mobile station MS#0 using the signal format shown in Fig. 5B (step S13). Fig. 5B shows the signal format used by the QoS agent to notify the radio network control station RNC (=signal indicative of  
15 information on desired base stations to which the mobile station is to be connected). This signal format includes an RNC address, a connection request command, a mobile station address, and information on desired bas stations to connect.

20 In this case, the QoS agent selects base stations to which the mobile station is to be connected by calculating the attenuation of a signal on the basis of the locations of the surrounding base stations and the mobile station as shown in Fig. 6, referencing the past connection history  
25 of the mobile station as shown in Fig. 7B, or combining together the methods shown in Figs. 6 and 7B.

In Fig. 6, at step S21, a distance attenuation is

calculated on the basis of the distance between each surrounding base station and the mobile station. At step S22, it is determined which base stations be combined together in order to satisfy the receiving quality.

5        Fig. 7A illustrates a past connection status history possessed by the QoS agent. The QoS agent stores the correspondences between the locations of mobile stations and receiving qualities and base stations to which the mobile station is to be connected, as tables. In Fig. 7B,  
10        at step S31, a history that satisfies the desired receiving quality is picked up. At step S32, the history of a mobile station located closest to desired base stations to which the mobile station is to be connected is picked up. At step S33, base stations which are shown in the picked-  
15        up histories to have been connected to the mobile station are selected.

Referring back to Fig. 4B, the radio network control station RNC duplicates a downlink transmitted signal, if any, and transmits it to the selected base stations (step  
20        S14).

The mobile station MS#0 receives and synthesizes signals transmitted by the base stations (step S15), thereby satisfying the desired downlink receiving quality.

25        In Embodiment 2, the mobile station MS#0 satisfies the desired quality by receiving and synthesizing the signals received from the base stations BS#0, #1, and #2,



but of course the present invention is not limited to this example.

[Embodiment 3]

Fig. 8A shows a mobile communication system for  
5 implementing receiving quality control for an uplink.  
This system comprises the radio network control station  
RNC, the base station BS, the mobile station MS, and the  
QoS agent. More specifically, Fig. 8A shows how the base  
station BS (including base stations #0 to #N), the mobile  
10 station MS#0, the radio network control station RNC, and  
the QoS agent are connected together according to  
Embodiment 3, and Fig. 8B shows the flow of communication  
control according to Embodiment 3.

In Embodiment 3, before transmitting information, the  
15 mobile station MS#0 transmits a desired uplink quality  
received by base stations and the location and  
transmittable maximum power of the mobile station, to the  
QoS agent using the signal format shown in Fig. 9A (step  
S41). The QoS agent selects base stations to which the  
20 mobile station is to be connected in order to satisfy this  
quality in such a way that the transmittable maximum power  
of the mobile station MS#0 is not exceeded (step S42), and  
notifies the mobile station of corresponding transmission  
power using the signal format shown in Fig. 9B (step S43).  
25 Further, the QoS agent requests the radio network control  
station RNC to synthesize a signal from the mobile station  
MS#0, using the signal format shown in Fig. 9C (step S44).

Furthermore, the QoS agent requests each base station to receive a signal from the mobile station MS#0, using the signal format shown in Fig. 9D.

5 In Embodiment 3, base stations to which the mobile station is to be connected can be selected using the means in Fig. 6 or 7B, described above, or a combination of these methods.

10 The mobile station MS#0 transmits a signal using the designated transmission power (step S46), and the radio network control station RNC synthesizes the signals received by the base stations (steps S47 and S48), thereby realizing the desired uplink receiving quality.

15 Fig. 9A, described above, shows the signal format used by the mobile station MS#0 to notify the QoS agent (=signal indicative of a desired receiving quality, a transmittable maximum power, and information on the location of the mobile station). This signal format includes a QoS agent address, a connection request command, a mobile station address, a desired uplink receiving quality, a maximum  
20 transmission power, and information on the location of the mobile station. Fig. 9B shows the signal format used by the QoS agent to designate transmission power that is to be used by the mobile station MS#0. This signal format includes a mobile station address, a transmission power  
25 designation command, and transmission power. Fig. 9C shows the signal format used by the QoS agent to notify the radio network control station RNC (= signal requesting

synthesis of signals). This signal format includes an RNC address, a signal synthesis request command, a mobile station address, and information from base station to be synthesized. Fig. 9D shows the format of a reception request signal transmitted to each base station by the QoS agent. This signal format includes the address of the base station, a reception request command, and a source mobile station address.

In Embodiment 3, the base stations BS#0, #1, and #2 each receive a signal from the mobile station MS#0, but of course the present invention is not limited to this example.

[Embodiment 4]

Fig. 10A shows another mobile communication system for implementing receiving quality control for the downlink. This system comprises the radio network control station RNC, the base station BS, the mobile station MS, and the QoS agent. More specifically, Fig. 10A shows how the base station BS (for simplification, the number of base stations is assumed to be two), the mobile station MS#0, the radio network control station RNC, and the QoS agent are connected together according to Embodiment 4, and Fig. 10B shows the flow of communication control according to Embodiment 4.

In Embodiment 4, it is assumed that at a certain time, the base station BS#0, constituting a cell #0, is communicating with the mobile station MS#0, which is

present within the cell #0 (step S51). The QoS agent measures the traffic in adjacent cells (step S52) and determines that the cell #1 has a low traffic and that a signal can be transmitted to the mobile station MS#0 in the cell #0. The QoS agent requests the radio network control station RNC to duplicate information transmitted to the base station BS#1 (step S53, S54, and S55). As a result, the mobile station MS#0 can receive and synthesizes signals from both the base stations BS#0 and BS#1 (step S56). Thus, if the signal power transmitted by each base station is assumed to be fixed, the receiving quality of the mobile station is improved.

As shown in Fig. 11, the duplicate request signal transmitted to the radio network control station RNC by the QoS agent includes an RNC address, a duplicate request command, a duplicate base station address, and a destination mobile station address.

On the other hand, in Embodiment 4, if the object is to keep the receiving quality of the mobile station constant, the transmission power of each base station can be reduced, thereby reducing interference with other mobile stations simultaneously communicating within the cell.

#### [Other Embodiments]

It is needless to say that the object of the present invention can be accomplished by providing a system or an apparatus with a recording medium (storage medium) in which

software program codes implementing the functions of the  
embodiments described previously are recorded so as to be  
readable by a computer, and causing a computer (or a CPU  
or an MPU) in the system or apparatus to read out the program  
5 codes stored in the recording medium and execute commands  
in accordance with the program codes. In this case, the  
program codes read out from the recording medium implement  
the functions of the embodiments described previously, and  
the recording medium having the program codes recorded  
10 therein constitutes the present invention. The recording  
medium having the program codes or variable data such as  
tables recorded therein may be, for example, a magnetic  
disk such as a floppy disk or a hard disk, any optical disk,  
any photo-magnetic disk, or any non-volatile memory card.  
15 The present invention has been described in detail  
with respect to preferred embodiments, and it will now be  
apparent from the foregoing to those skilled in the art  
that changes and modifications may be made without  
departing from the invention in its broader aspect, and  
20 it is the intention, therefore, in the apparent claims to  
cover all such changes and modifications as fall within  
the true spirit of the invention.